# DIGITUS®

## USB-C™ - HDMI Graphics Adapter Cable, UHD 8K / 60 Hz



Quick Installation Guide
DA-70822

#### **Table of Contents**

1.	Introduction	2
2.	Main Features	2
_		_
3.	Package Contents	3
1	Specification	2
٠.	Specification	

#### 1. Introduction

The DIGITUS® USB-C™ to HDMI adapter cable enables you to connect your notebook or tablet to a monitor, projector or TV device to the USB-C™ connection. No additional adapters are required. Depending on the source device, this cable supports resolutions of up to 8K / 60 Hz incl. 3D and HDR10 support. This cable also supports data transfer rates of up to 5 Gbps as well as the USB 3.1 features. You won't need any additional adapters or converters. Simply use the DIGITUS® adapter cable USB-C™ on HDMI®.

#### 2. Main Features

- Universal USB-C™ Graphics Adapter with HDMI Output
- Full 8K resolution at 60 Hz
- With integrated audio transmission for a Dolby Surround sound experience
- Supports HDR10
- Supports 3D displays
- · High-quality aluminum housing
- Power supply is provided via the USB-C<sup>™</sup> port
- Plug and Play no driver installation required

#### 3. Package Contents

- 1 x USB-C™ HDMI Graphics Adapter Cable, UHD 8K / 60 Hz
- 1 x Quick installation guide

### 4. Specification

Technical				
Video resolution	8K Ultra HD (UHD) resolution with			
	7680 x 4320p / 60Hz			
Data transfer rate	5 Gbps			
Weight	34 g			
Color depth	12 bit			
Color	Space grey			
Housing	High-quality aluminum housing			
Cable adapter length	20 cm			
Dimension (LxWxH)	210 x 31,5 x 14			
Supports	HDR10			
	3D displays			
	HDCP 1.4 / 2.2			
	YUV 4:4:4			
	HDMI 1.4b			
	Consumer Electronic Control (CEC)			
	Lip Sync (audio/video synchronization)			
	21:9 Cinemascope			
	32 channel audio			
	8-channel LPCM, 192 kHz,			
	24-bit audio capability			
	DTS-HD Master Audio bitstream			
	EDID 1.6 (device recognition)			
	DVI Version 1.0			
Supported operating	Android 10.0, Chrome OS 86.0, macOS			
systems	11.0.1, Windows 8.1, Linux 5.4,			
	iPad Pro (3rd) or higher versions			

	Suitable for Pcs or notebooks with USB-
	C™ or Thunderbolt3 port
Operating humidity	20% - 80% RH
Operating	-10°C ~ +50°C
temperature	

Manufacturer's notice: Not all USB- $C^T$  ports support all the features of the USB Type- $C^T$  standard. Make sure that your notebook's USB- $C^T$  port supports the DisplayPort Alternate Mode (DP Alt Mode). The video output capabilities depend on your notebook's graphic card and the connected monitor. Some screens also limit the available resolution.

Hereby ASSMANN Electronic GmbH declares that the Declaration of Conformity is part of the shipping content. If the Declaration of Conformity is missing, you can request it by post under the below mentioned manufacturer address.

#### www.assmann.com

Assmann Electronic GmbH Auf dem Schüffel 3 58513 Lüdenscheid Germany

