

WHITE WEASEL[™] MOBILITY 3G | 4G | LTE ACCESSPOINT & ROUTER Quick Installation Guide

Hardware Installation

A. Hardware configuration



B. Installation Steps

Note: DO NOT connect the router to power before performing the installation steps below.

Step 1.

Plug a USB modem into USB port.



Step 2.

Insert RJ45 cable into LAN Port on the back panel of the router. Then plug the other end of into computer.



Plug the power jack into the receptor on the back panel of the router. Then plug the other end into a wall outlet or power strip.



Getting Started with Easy Setup Utility

There are two approaches for you to set up the WiFi Combo Router quickly and easily. One is through executing the provided Windows Easy Setup Utility on your PC, and the other is through browsing the device web pages and configuration.

Easy Setup by Windows Utility

Step 1:

Install the Easy Setup Utility from the provided CD then follow the steps to configure the device.

Step 2:

Select Language then click "Next" to continue.

Step 3:

Then click the "Wizard" to continue.





Step 4 :

Click "Next" to continue.



Step 5:

Select Wireless Enable, and then click "Next" to continue.

Help	< Back Next >	Cancel
This step will setup your basic wire	less network settings.	
This will provide you with a basic works later.	able setting for your wireless. You can also	select to do it
Wireless: Ena Dis Ena	able 💙 able	
Do not set at this time.		
Help	< Back Next >	Cancel
This step will setup your basic wirel	ess network settings.	

Step 6:

Enter SSID, Channel and Security options, and then click "Next" to continue.

Help	< Back Next > Cancel			
This step will setup your basic wireless network settings.				
Please assign the parameters to your the Gateway's configuration page.	wireless networking. If you need more settings, please login to			
SSID: Channel: Security: Key:	Befault 11 WEP ***********			
Help	< Back Next > Cancel			

Step 7:

Step 8:

Click" Let me select WAN service by myself" to select WAN service manually.

Select 3G Service by clicking

3G icon to continue.



Step 9-1 :

Select "Auto-Detection" and the Utility will try to detect and configure the required 3G service settings automatically. Click "Next" to continue.

WAN 30	Setting 3 Service				21
Please i	nput the WAN service in	formation.			
	Dial-Up profile		🔿 Manual		
	FIN Code: APN: Dialed Number: Username: Password:			(Optional) (Optional)	
Hel	þ		< Back	Next >	Cancel

Step 9-2 :

Or you can select "Manual" and manually fill in the required 3G service settings provided by your ISP. Click "Next" to continue.

WAN Setting 3G Service				21
Please input the WAN service info	ormation.			
-Dial-Un profile				
Auto-Detection		 Manual 		
PIN Code:	internet		(Optional)	
APN:	1234		(Optional)	
Dialed Number:	*99#			
Username:	Admin			
Password:	1234]	
Help		< Back	Next >	Cancel
Save Settings				
The settings will be saved to the F	louter and re	eboot at the next step.		

Step 10:

Click "Next" to save your setting.

Help		< Back	Next > Cancel
Save S	ettings		2
The setti	ngs will be saved to the Router and 1	eboot at the next step.	
	SSID:default Channel:11 Security:WEP		
	WAN Setting (36 Service) APN:1234 PIN Code:internet		
	Dialed Number:*99# Username:Admin Password:1234		Modify Settings
Help	•	< Back	Next > Cancel

Step 11:

The WiFi Combo Router is rebooted to make your entire configuration take effect.

Save Settings	2	
Reboot router		
Help	< Back Next > Cancel	•

Step 12 :

Click "Next" to test the Internet connection or you can ignore test.



Step 13 :

Click "Next" to test WAN Networking service.

Save Settings				
Settings have been saved and in	itialized.			
The next step will test your Inte	met connection	. Or you can choos	e to ignore the test	
Help		< Back	Next >	Cancel
Setup Completed				21
The Router is configured, and t	he WAN servic	e functionality is w	orking	
			_	
		4		
		`_		

Finish

Step 14 : Setup is completed.