



GIGABIT ETHERNET NETWORK SWITCH

DN-8021B

24-Port Switch Packing List :

Before you start installing 24 Gigabit Web Smart Switch, please verify that the package contains the following items:

- 24-Port GbE Web Smart Switch
- AC Power Cord
- Mounting Accessory (for 19" Rack Shelf)
- User's Guide CD-ROM

Please notify your sales representative immediately if any of the aforementioned items is missing or damaged.

Power Requirements : AC Line

Voltage	:	100~240 VAC
Frequency	:	50~60 Hz
Consumption	:	30W

Quick Installation :

1. Install the switch in the rack with mounting accessory.
2. Connect the switch to an AC power source.
3. The port 1~24 connector is RJ-45 jack on the switch. Use Category 5 UTP cable to connect between the switch and end station.
4. The port 21~24 includes two types of media --- TP and SFP fiber module; they support TP or fiber with auto-detected function.
5. The default values of the switch are as follows:

IP Address	:	192.168.1.1
Subnet Mask	:	255.255.255.0
Default Gateway	:	192.168.1.254
Password	:	admin

User can use web to configure the switch with the default IP address and password in the first configuration. Please refer to User's Guide contained in CD-ROM for details on the setting of parameters. User's manual is filed under the path: \manual of the CD-ROM.