


DIGITUS® CAT 6, Class E_A Keystone Module, shielded





Abstract

DIGITUS® CAT 6 Class E_A Keystone Module, shielded, toolfree installation

Features

- CAT 6 Class E_A for up to 500 MHz
- Fully shielded
- Suitable for 10 Gbit Ethernet
- Quick and easy installation without any special tool
- Tool free connection via LSA, color coded according EIA/TIA 568 A&B
- RJ45 outlet for mounting in Patch Panel
- Opening dimensions according to Keystone standard 19.35x14.8 mm
- Compact design allows the installations of 24 pieces in a row of 483 mm (19") 1U Panels
- Cable entry: Rear side
- Housing: Nickel-plated, impact-resistant zinc housing
- Contacts: Phoshor, bronzeIDC contacts: Phoshor, bronze
- Layer: 50 μm gold over 40 μm nickel
- Cable connection type: Tool free with cable hatch for strong/flexible conductions AWG 23-26
- Wiring standard: EIA/TIA 568 A/B
- Conformity: Category 6_A / 10GBase-T Channel, ANSI/EIA/TIA 568C.2.1:2002, ISO/IEC 11801:2002
- Certification: GHMT, Delta - Dimensions: 18x24x41 mm
- Weight: ca. 23 g

Product Overview

The fully downward compatible CAT 6_A Keystone Module makes an easy installation in combination with excellent measurements possible. The high quality ensures the usage with the most demanding applications like 10Gbase-T. The innovative housing design offers quick and safe wire terminations without any special tool. Its compact form allows an installation of 24 Keystone Modules in a row with a 1U Patch Panel. These facts assure an uncomplicated mounting and marking as well as a high reliability.


Product Number Information

DN-93612 DIGITUS® CAT 6 Keystone Module, shielded, Class E_A, RJ45 to LSA, toolfree installation





Product Images








Technical Drawings














Assmann Electronic GmbH, Auf dem Schüffel 3, 58513 Lüdenscheid, Germany, info@assmann.com, printing errors, falsities and technical changes remain reserved