

## DIGITUS<sup>®</sup> Metering Power Distribution Unit (PDU)



✓ 19" rack mount, 1U

✓ Network connection RJ45

✓ Lighted LCD screen

✓ Minimum own consumption

### Abstract

DIGITUS<sup>®</sup> Metering Power Distribution Unit (PDU), with aluminum profile, 7x safety outlets

### Features

- 1x Power connection (safety plug, max. 16 A)
- Supply cable: safety plug, 3 m
- 7x safety outlets, max. 16 A
- Network connection RJ45 (10/100 Mbit)
- 19" rack mountable
- Height Unit: 1U
- Weight: ca. 1.5 kg
- Operating temperature: 0-50 °C (non-condensing)
- Metering of power, electric tension, phase angle, power-factor, frequency, active-, apparent- and idle power
- 2 energy counter, one counter is permanently counting, the other one is resettable
- Lighted LCD screen
- HTTP 1.1, E-Mail, DHCP, SNMPv1 (Traps), SNM Ov2c (Traps), Syslog
- Firmware update possible per ethernet while in operation
- Minimum own consumption
- Developed and produced in Germany

### Product Overview

The DIGITUS<sup>®</sup> Metering PDU enables metering of electrical appliances through TCP/IP network.

The front panel disposes of seven load outlets with safety connector. There are two energy meters integrated.

Features like the lighted LCD screen, minimum own consumption and the possibility of a firmware updated while in operation make this PDU to the optimized, 19" rack mountable device.

## Product Number Information

DN-95601 DIGITUS<sup>®</sup> Metering PDU, 1U, rackmountable, max. 16 A, 7x safety outlets, 1xRJ45, LCD panel, measuring power, electricity, tension

## More Power Distribution Units (PDU) from DIGITUS<sup>®</sup>

DN-95602 DIGITUS<sup>®</sup> Metering PDU, 1U, rackmountable, max. 10 A, 8x IEC C13, 1x RJ45, LCD Panel, measuring power, electricity, tension

DN-95401 DIGITUS<sup>®</sup> 1U Aluminum PDU, rack mount, 16 A, 4000 W, 250 VAC 50/60 Hz, 8x safety outlets

DN-95402 DIGITUS<sup>®</sup> 1U Aluminum PDU, rack mount, 16 A, 4000 W, 250V AC 50/60 Hz, 7x safety outlets, switch

DN-95403 DIGITUS<sup>®</sup> 1U Aluminum PDU, rack mount, 16 A, 4000 W, 250 VAC 50/60 Hz, 7x safety outlets, overload protection

DN-95404 DIGITUS<sup>®</sup> 1U Aluminum PDU, rack mount, 10 A, 2500 W, 250VAC 50/60 Hz, 10x IEC C13, overload protection

DN-95405 DIGITUS<sup>®</sup> 1U Aluminum PDU, rack mount, 2x 16 A, 250 VAC 50/60 Hz, 12x safety outlets, overload protection

DN-95407 DIGITUS<sup>®</sup> 1U Aluminum PDU, rack mount, 16 A Plug, 250 VAC 50/60 Hz, 7 way safety outlet, with switch, surge protection

DN-95408 DIGITUS<sup>®</sup> 1U Aluminum PDU, 6 way IEC C19, power cable IEC C20

DN-95411 DIGITUS<sup>®</sup> 1U Aluminum PDU, rack mount, for 254 mm (10") cabinet, 16 A, 4000 W, 250 VAC 50/60 Hz, 3x safety outlets

A-19-STRIP42-1 18 way outlet strip - 42U in length vertical, dual circuit, aluminum, 2x 16 A, circuit breaker, vertical mount

## Product Images

