

## DIGITUS<sup>®</sup> Metering Power Distribution Unit



✓ 19" rack mount, 1U

✓ Network connection RJ45

✓ Lighted LCD screen

✓ Minimum own consumption

### Abstract

DIGITUS<sup>®</sup> Metering Power Distribution Unit, with aluminum profile, 8x outlets IEC C13

### Features

- 1x Power connection (CEE 7/7 plug, max. 16 A)
- Supply cable: CEE 7/7, 3 m
- 8x outlet IEC C13, max. 10 A
- Network connection RJ45 (10/100 Mbit)
- 19" rack mountable
- Height Unit: 1U
- Weight: ca. 1.5 kg
- Operating temperature: 0-50 °C (non-condensing)
- Metering of power, electric tension, phase angle, power-factor, frequency, active-, apparent- and idle power
- 2 energy counter, one counter is permanently counting, the other one is resettable
- Lighted LCD screen
- HTTP 1.1, E-Mail, DHCP, SNMPv1 (Traps), SNM Ov2c (Traps), Syslog
- Firmware update possible per ethernet while in operation
- Minimum own consumption
- Developed and produced in Germany

### Product Overview

The DIGITUS<sup>®</sup> Metering PDU enables metering of electrical appliances through TCP/IP network.

The front panel disposes of eight load outlets with IEC C13 connector. There are two energy meters integrated.

Features like the lighted LCD screen, minimum own consumption and the possibility of a firmware updated while in operation make this PDU to the optimized, 19" rack mountable device.

## Product Number Information

DN-95602 DIGITUS<sup>®</sup> Metering PDU, 1U, rackmountable, max. 10 A, 8x IEC C13, 1x RJ45, LCD Panel, measuring power, electricity, tension

## More Power Distribution Units (PDU) from DIGITUS<sup>®</sup>

DN-95601 DIGITUS<sup>®</sup> Metering PDU, 1U, rackmountable, max. 16 A, 7x CEE 7/7, 1xRJ45, LCD panel, measuring power, electricity, tension

DN-95401 DIGITUS<sup>®</sup> 1U Aluminum PDU, rack mount, 16 A, 4000 W, 250 VAC 50/60 Hz, 8x outlet CEE 7/7

DN-95402 DIGITUS<sup>®</sup> 1U Aluminum PDU, rack mount, 16 A, 4000 W, 250V AC 50/60 Hz, 7x outlet CEE 7/7, switch

DN-95403 DIGITUS<sup>®</sup> 1U Aluminum PDU, rack mount, 16 A, 4000 W, 250 VAC 50/60 Hz, 7x outlet CEE 7/7, overload protection

DN-95404 DIGITUS<sup>®</sup> 1U Aluminum PDU, rack mount, 10 A, 2500 W, 250VAC 50/60 Hz, 10x IEC C13, overload protection

DN-95405 DIGITUS<sup>®</sup> 1U Aluminum PDU, rack mount, 2x 16 A, 250 VAC 50/60 Hz, 12x CEE 7/7, overload protection

DN-95407 DIGITUS<sup>®</sup> 1U Aluminum PDU, rack mount, 16 A Plug, 250 VAC 50/60 Hz, 7 way, with switch, surge protection

DN-95408 DIGITUS<sup>®</sup> 1U Aluminum PDU, 6 way IEC C19, power cable IEC C20

DN-95411 DIGITUS<sup>®</sup> 1U Aluminum PDU, rack mount, for 254 mm (10") cabinet, 16 A, 4000 W, 250 VAC 50/60 Hz, 3x outlet CEE 7/7

A-19-STRIP42-1 18 way outlet strip - 42U in length vertical, dual circuit, aluminum, 2x 16 A, circuit breaker, vertical mount

## Product Images

