

## legrand Daker DK 1kVA Online UPS



✓ 19" rack mount or tower installation

✓ 1kVA

✓ 6x IEC C13

✓ Safety class acc. IEC 529: IP 20

### Abstract

legrand Daker DK 1kVA Online UPS, 6x IEC C13

### Features

- Weight: 16 kg
- 2x IEC C13 programmable outputs, 4x IEC C13 outputs
- Safeguards: Overload, bypass, interrupt of working by termination of autonomic time and overheating
- Operating temperature range: 0 up to +40 °C
- Operating moisture range: 20 up to 80 % non-condensation
- Safety class according IEC 529: IP 20
- Noise level in 1 m distance: < 50 dB/A
- Nominal input voltage: 230 V
- Nominal output voltage: 230 V ± 1%
- Range of nominal input voltage: 160 V up to 288 V
- Nominal input frequency: 50 or 60 Hz ± 5Hz
- Maximum input volt power: 5.2 Arms
- Number of input phases: Monophase
- Number of output phases: Monophase
- Battery operation: Sine-shaped
- Operating type: On line - double converter
- Active output power with nominal load: 800 W
- Apparent output power with nominal load: 1 kVA
- Overload capacity: 105% non-stop operation, 120% for 30 seconds, 150% for 10 seconds
- Battery operating autonomy: 10 minutes
- Battery charging time: 4 to 6 hours on 80% of loading
- 3 maintenance-free, leaded and sealed batteries, 12 V 9 Ah
- Electromagnetic compatibility, Immunity - Emissions: According to EN 62040-2
- Safeguards: According to EN 62040-1
- Characteristic power: According to EN 62040-3

## Product Overview

The legrand Daker On-Line UPS enclosures in combirack are useable as tower or rackmountable. With the display you can control all system-relevant functions and check the status of the UPS enclosure e.g. workload, remaining bridging time and system issues. With the IEC outlets, USB, RS232, SNMP-Slot and a LCD-Display, the USP enclosures are the best solution for professional use. The models "A-17060" and "A-17061" can be endowed with additional battery racks for increasement of bridging time. An additional battery loading enclosure is integrable in every battery rack to ensure a safer and faster loading of the battery system.

## Product Images



## Product Number Information

A-17060 legrand Daker DK 1kVA Online UPS, IEC outlets, USB, RS232, SNMP-slot, LCD display, Hot Swap Battery, 440x405x88 mm (WxDxH)

## More legrand Daker DK Online UPS Enclosures

- A-17061 legrand Daker DK 2kVA Online UPS, IEC outlets, USB, RS232, SNMP-slot, LCD display, Hot Swap Battery, 440x650x88 mm (WxDxH)
- A-17062 legrand Daker DK 3kVA Online UPS, IEC outlets, USB, RS232, SNMP-slot, LCD display, Hot Swap Battery, 440x650x88 mm (WxDxH)
- A-17063 legrand Daker DK 4.5kVA Online UPS, IEC outlets, USB, RS232, SNMP-slot, LCD display, Hot Swap Battery, 440x680x176 mm (WxDxH)
- A-17064 legrand Daker DK 6kVA Online UPS, IEC outlets, USB, RS232, SNMP-slot, LCD display, Hot Swap Battery, 440x680x176 mm (WxDxH)

## Accessories

A-17065	legrand Daker 1kVA battery pack, lifetime extensions for A-17060, 440x405x176 mm (WxDxH)
A-17066	legrand Daker 2kVA battery pack, lifetime extensions for A-17061, 440x650x88 mm (WxDxH)
A-17067	Rack Assembly Kit (2U), rack mount, telescope rails 2U, incl. mounting material
A-17068	legrand Daker external bypass 1-3, 2U, incl. mounting material, for A-17060, A-17061, A-17062
A-17069	legrand Daker contact interface card, card with potential free contacts for assembly in SNMP slot
A-17070	legrand Daker SNMP CS 121B SK card, network SNMP adapter, incl. 1x RCCMD license
A-17071	legrand Daker RCCMD Multi OS license, RCCMD Multi-OS Agent Shutdown Software