

DIGITUS® Modular Couplers, unshielded



Abstract DIGITUS[®] Modular Couplers, unshielded, RJ12 6P6C or RJ45 8P8C

Features

- 2x RJ jack
- Assignment: 1:1
- Plastic housing
- Material PCB: FR4, 1.2 mm thickness
- Contacts coating: Nickel, gold plated 0.6 μ
- Mating cycles: ≥ 750
- Operating temperature: -40 °C up to +80 °C

Product Overview

The unshielded modular couplers from DIGITUS[®] consist of 2 RJ jacks. They are available as RJ12 6P6C or RJ45 8P8C. The assignment is 1:1.

Product Number Information

AT-A 6/6	DIGITUS® Modular Coupler, RJ12, unshielded, 6P6C to 6P6C, color white
AT-A 6/6-BL	DIGITUS [®] Modular Coupler, RJ12, unshielded, 6P6C to 6P6C, color black
AT-A 8/8	DIGITUS® Modular Coupler, RJ45, unshielded, 8P8C to 8P8C, color white

More Modular Adapters

AT-AG CX2	DIGITUS [®] CAT 5e Patch cable adapter, shielded, 2x RJ45 jack to 1x RJ45 plug,
	cable length 0.19 m, assignment 1:1
DN-93904	DIGITUS [®] CAT 5e Patch cable adapter, shielded, 2x RJ45 jack to 1x RJ45 plug,
	cable length 0.19 m, assignment: 1-1, 2-2, 3-3, 4-1, 5-2, 6-6, 7-3, 8-6
AT-AG 2X8/8	DIGITUS [®] CAT 5e Modular Coupler, s, 2x RJ45 to 1x RJ45, threefold coupler
AT-AG 8/8 C6S	DIGITUS [®] Modular Coupler, 8P8C, 1:1, shielded, CAT6, metal housing
AT-AG6 8/8CROSS	DIGITUS® CAT 6 Modular Coupler, shielded, RJ45 to RJ45, crossover version
DN-93901	DIGITUS [®] CAT 5e Modular Coupler, shielded, RJ45 to RJ45
A-CP-LINK	CAT 7 S-FTP RJ45 adapter, shielded, S/FTP AWG27/7 LSZH, pin assignment T568B,
	IEC 60603-7-51, color blue