# DIGITUS®

# USB Type-C™ 4K 2-in-1 DisplayPort™ + VGA Graphics Adapter



Quick Installation Guide
DA-70827

#### **Table of Contents**

1.	Introduction	. 2
2.	Main Features	. 2
3.	Package Contents	. 3
	<b>G</b>	
4.	Specification	. 3

#### 1. Introduction

With the DIGITUS® USB-C™ to DisplayPort™ + VGA Adapter Cable, you can connect a monitor, projector or TV with DisplayPort™ or VGA connection to the USB-C™ connection of your notebook or tablet. No additional adapters are required. Depending on the source device, this cable supports resolutions of up to 4K/30 Hz. Thanks to Plug and Play, you don't have to install any drivers or change any settings – Just plug in and get started. You won't need any additional adapters or converters. Simply use the DIGITUS® adapter cable USB-C™ to DisplayPort™ + VGA adapter cable.

#### 2. Main Features

- Universal USB-C™ Graphics Adapter with DisplayPort™ and VGA
   Output
- Full 4K resolution at 30 Hz
- With integrated audio transmission for a Dolby Surround sound experience (except for VGA)
- High-quality aluminum housing
- Power supply is provided via the USB-C<sup>™</sup> port
- Plug and Play no driver installation required

### 3. Package Contents

- 1 x USB Type-C<sup>™</sup> 4K 2-in-1 DisplayPort<sup>™</sup> + VGA Graphics Adapter
- 1 x Quick installation guide

## 4. Specification

Technical		
Video resolution	4K Ultra HD (UHD) resolution with	
	4096 x 2160p / 30Hz	
Power supply	Power supply is provided via the	
	integrated USB-C™ interface on the	
	adapter	
Weight	50 g	
Color depth	12 bit	
Color	Black	
Housing	High-quality aluminum housing	
Length	20 cm	
Dimension (LxWxH)	200 x 62 x 15.2 mm	
Supports	HDCP 2.2	
	DisplayPort™ 1.4	
	HDMI® 1.4b	
	Lip Sync (audio/video synchronization)	
	21:9 Cinemascope	
	8-channel LPCM, 192 kHz, 24-bit audio	
	capability	
	DTS	
	EDID 1.6 (device recognition)	
Supported operating	Android 10.0, Chrome OS 86.0, macOS	
systems	11.0.1, Windows 8.1, Linux 5.4,	
	iPad Pro (3rd) or higher versions	
Operating humidity	20% - 80% RH	

Operating	-10°C ~ +50°C
temperature	

Manufacturer's notice: The video output capabilities depend on your notebook's graphic card and the connected monitor. Some screens also limit the available resolution. Your device equipped with USB-C™ must support the DisplayPort™ video mode (DP Alt Mode) in order to be compatible with this adapter/converter.

Hereby ASSMANN Electronic GmbH declares that the Declaration of Conformity is part of the shipping content. If the Declaration of Conformity is missing, you can request it by post under the below mentioned manufacturer address.

#### www.assmann.com

Assmann Electronic GmbH Auf dem Schüffel 3 58513 Lüdenscheid Germany

