

DIGITUS® PLUG&VIEW

safe & secure – anywhere. anytime.

DIGITUS® Plug&View OptiGuard

DN-16049
EAN 4016032362944



More information
about this product
in your language
with QR-code or on
www.plug-view.com



DIGITUS® Plug&View app
for Apple iOS and Google Android



This IP camera from the Plug&View Series of DIGITUS® is the new guardian for your garden, garage yard or entrance area. The OptiGuard is thanks to its IP66-housing ideally suited for outdoor use. It is as narrow as inconspicuous and gives you a focused view on lonely corners or potential entrances on your property. The 2-megapixel CMOS sensor with infrared LEDs provides superior video resolution day and night. So you can go sleep in peace. The Plug&View camera is compatible with PC, notebook, and thanks to the free DIGITUS® Plug&View app also with a tablet or smartphone, which enables you to retrieve the surveillance images on the road at any time. The installation is performed easily and quickly for example via QR code scanning. The camera can be operated wirelessly over wireless LAN, the latest 11n standard ensures a liquid transfer.

Your Plug&View IP camera with outdoor-appropriate IP66-housing and simple installation

- 3 easy installation steps: 1. Establish network connection, 2. Install app or register camera on www.plug-view.com, 3. Ready to go!
- Integrated 2 GB storage for recording videos and snapshots
- Outdoor bullet camera for day & night use
- Low-latency video streaming with H.264 compression format

- 2 megapixel video resolution (Full HD 1920 x 1080, HD720 1280 x 720)
- IP66 housing design for outdoor use
- Integrated 2 GB storage for recording videos and snapshots
- Wireless LAN according to the newest 11n standard for fluent image transmission
- Low-latency video streaming with H.264 compression format
- Simple and fast installation with P2P support & QR-code-scanning
- Powerful mobile surveillance supporting iOS and Android devices
- IR-LEDs and IR cut filter included for day & night surveillance
- LAN speed: 10/100Base-TX Ethernet
- Suitable for the most common browsers
- Mounting kit included for easy installation
- Advanced motion detection, record and save events via e-mail/FTP/Google Drive
- Supports up to 25fps video frame rate at HD720 and 15fps at Full HD
- Operating temperature: -20 to +60 °C
- Power source (±10 %): DC12 V / 1 A
- Supports DIGITUS® Plug&View app for smartphone and tablet access
- Lens: F1.5 / 3.6 mm
- Horizontal viewing angle: 69°
- WPS (Wireless Protected Setup) function provides fast, easy, and secure wireless encryption
- Minimum system requirement Internet: DSL 1000 (1.024kBit download / 384kBit upload)
- Minimum system requirement smartphone access: 3G network connection
- Dimensions (mm): 180 (L) x 60 (W) x 65 (H)

Verpackungsinhalt:

- IP camera
- Product support CD-ROM
- Mounting kit
- Power Supply
- with 2 GB internal storage

