

## **DIGITUS® Unmounted Network Cabinets**



- ✓ 1.5 2 mm strong sheet steel
- ✓ IP 40 rating
- ✓ Loading capacity up to 400 kg
- ✓ Unmounted flat pack version

### **Abstract**

DIGITUS® Network Cabinets, unmounted, 600 mm and 800 mm depth

### **Features**

- 1.5 mm 2 mm strong sheet steel with a high loading capacity, powder coated
- Ventilation slots for active and passive ventilation and exhaustion
- IP 40 rating
- Safety-glass door with steel frame, lockable; optionally available with two openable doors
- Loading capacity up to 400 kg
- Back door lockable
- 483 mm (19") profile rails on the front side, adjustable in depth
- Cable entry in the middle of the bottom with movable sheet and rubber sealing
- Leveling feet, adjustable in height
- Including set of 28x 483 mm (19") assembly screws
- Roof module for ventilation unit
- IEC 297-2, DIN 41494/Part 7, DIN 41491/Part 1, EN 60950, VDE 0100
- Extensive range of accessories available



#### **Product Overview**

The DIGITUS® Network Cabinet SoHo series is designed and produced for cabling and networking components. They provide maximum optimization resulted to an optimum performance in between quality and added value. Each cabinet is designed with strength, ease of use and aesthetics in mind.

Features such as one unit marking on the mounting profiles, easy and quick release of the doors, fully adjustable front and rear profiles of the cabinet make the product extremely attractive to installers.

The incredible design of the SoHo series is rounded up with the use of a framed smoked safety glass front door fitted with a swing handle lock. Door hinging can be quickly reversed left to right.

The SoHo series is available in 3 heights from 22 units up to 42 units.

A various size of 600 mm and 800 mm depth are also in the portfolio of the series. Each cabinet includes a lockable front door and a lockable steel back door.

Furthermore, 2 sets of adjustable mounting profiles are equipped and the roof is prepared for fan trays as well as cable entry brush strips are included.

A huge range of DIGITUS® accessories is available to customize the cabinet due to the needs of the end-user.

#### **Product Number Information**

DN-19 22U-6/6-EC-1	DIGITUS® 22U network cabinet, unmounted, 1164x600x600 mm, color grey (RAL 7035)
DN-19 32U-6/6-EC-1	DIGITUS® 32U network cabinet, unmounted, 1609x600x600 mm, color grey (RAL 7035)
DN-19 42U-6/6-EC-1	DIGITUS® 42U network cabinet, unmounted, 2053x600x600 mm, color grey RAL 703
DN-19 22U-6/8-EC-1	DIGITUS® 22U network cabinet, unmounted, 1164x600x800 mm, color grey (RAL 7035)
DN-19 32U-6/8-EC-1	DIGITUS® 32U network cabinet, unmounted, 1609x600x800 mm, color grey (RAL 7035)
DN-19 42U-6/8-EC-1	DIGITUS® 42U network cabinet, unmounted, 2053x600x800 mm, color grey (RAL 7035)

# **Dimensions Overview**


Dimensions (Distances)			
Distance between	600 mm depth cabinets	800 mm depth cabinets	
Front door & profile rail	60 mm	70 mm	
Back door & profile rail	80 mm	90 mm	
Front and rear profile rail	370 mm	570 mm	





# **Product Images**



# **Technical Drawings**







Assmann Electronic GmbH, Auf dem Schüffel 3, 58513 Lüdenscheid, Germany, info@assmann.com, printing errors, falsities and technical changes remain reserve