DIGITUS®

DRAADLOZE 300N USB 2.0 INTERNETADAPTER



Snel installatiegids DN-70542 Rev.2 • DN-70543 Rev.2

Het stuurprogramma installeren

Volgt u de onderstaande instructies op om uw nieuwe draadloze USB-omvormer te installeren:

- 1. Steek de draadloze USB netwerkadapter in een vrije USB 2.0 poort van uw computer. Vergeet a.u.b. niet dat de USB stekkerzijde directioneel is, draai de USB adapter dus om als het niet in de USB poort past.
- 2. Het onderstaande scherm zal op uw computer verschijnen, klik op 'Cancel / Close'. Windows 7/8/10 Plaats het stuurprogramma in uw cd-rom.

Driver Software Installation		X
Installing device driver so	ftware	
802 11 p WLAN	Waiting for user input	-
	waiting for user input	
	Close	

3. U zult "auto-run" zien staan zoals op het onderstaande scherm te zien is. U zult "auto-run" zien staan zoals op het onderstaande scherm te zien is. Zo niet, dubbelklik a.u.b. op 'autorun.exe' op de CD.

DIGITUS®		- ×
	Install Driver	
	User Manual	
	Exit	

Klik op 'Install Driver' om de installatieprocedure op te starten.

4. Vervolgens zal de installatie wizard verschijnen. Klik op 'Next' om te vervolgen.



5. Steek de draadloze USB netwerkadapter (DN-70542/DN-70543) in een USB 2.0 poort van uw computer, het systeem zal de nieuwe hardware herkennen en de drivers automatisch installeren.



 De computer zal worden verzocht te herstarten zodra de installatie is voltooid. U kunt vervolgens op '<u>Finish</u>' klikken om de computer te herstarten en de installatie van de driver af te ronden.

REALTEK 11n USB Wireless LAN Software		
	InstallShield Wizard Complete The InstallShield Wizard has successfully installed REALTEK. 11n USB Wireless LAN Software. Before you can use the program, you must restart your computer. • Yes, I want to restart my computer now. • No, I will restart my computer later. Remove any disks from their drives, and then click Finish to complete setup.	
	K Back Finish Cancel	

7. Klik nadat de installatie is voltooid op het adapterprogramma op uw taakbalk of in de programmafolder. Klik op "available networks", selecteer het draadloze toegangspunt waarmee u verbinding wilt maken en klik op de "Add to Profile" toets.

REALTEK 11n USB W	ireless LAN Utili	ity			
Refresh(R) Mode(M) Abou	it(A)				
🖃 🦞 MyComputer	General Profile	Available Network Statu:	s Statistics V	Vi-Fi Protect Setup	
Realtek RTL818	Available Netw	/ork(s)			
	SSID	Channel	Encryption	Network Authentication	Signal 1
	IN HLY96C	1	AES	WPA Pre-Shared Key	88% Ir
	INETCORE	1	None	Unknown	42% Ir
	IN HLY3F	6	TKIP	WPA Pre-Shared Key	26% Ir
	I"QA300M	6	None	Unknown	58% Ir
	1 WR2880	6	None	Unknown	8% Ir
	tilletink tilletink	11	None	Unknown	62% Ir
	<				>
		Refresh		Add to Profile]
	Note Double cl	ick on item to join/creat	e profile.		
✓ Show Tray Icon Radio Off		Disable AcWindows	lapter Zero Config		Close

8. Vul eventueel de nodige beveiligingsinformatie in en klik vervolgens op "OK" om verbinding te maken met het draadloze netwerk.

Wireless Network Properties:		
Profile Name: HLY96C	802.1x configure	
Network Name(SSID): HLY96C	EAP TYPE :	
	GTC	~
	Tunnel : Privision Mode :	
☐ This is a computer-to-computer(ad hoc) network; wireless access points are not used.		<u>~</u>
Channel: 1 (2412MHz) 🗸		
	Username :	
Wireless network security		
This network requires a key for the following:	Identity :	
Network Authentication: WPA-PSK 🛛 👻		
Data encryption: AES	Domain :	
	Password :	
Key index (advanced): 1	Certificate :	
Network key:		~
******	PAC : Auto Select PAC	
Confirm network key:		~

OK Cancel		

9. Zodra de verbinding eenmaal is geslaagd, zal het statusscherm verschijnen.

🙁 REALTEK 11n USB Wireless LAN Utility		
Refresh(R) Mode(M) Abou	t(A)	
🖃 🥊 MyComputer	General Profile Available Network Status Statistics Wi-Fi Protect Setup	
	Status: Associated	
	Speed: Tx:150 Mbps Rx:150 Mbps	
	Type: Infrastructure	
	Encryption: AES	
	SSID: HLY96C	
	Signal Strength: 74%	
	Link Quality:	
	Network Address:	
	MAC Address: 00:E0:4C:71:00:01	
	IP Address: 192.168.1.139	
	Subnet Mask: 255.255.255.0	
	Gateway:	
	ReNew IP	
🗹 Show Tray Icon	Disable Adapter Close	
🔲 Radio Off	Windows Zero Config	