

DIGITUS® CAT 6A Keystone Module, unshielded



✓ Category 6_A

✓ Unshielded

✓ 500 MHz, 10 Gbit

✓ slim design

Abstract

DIGITUS® CAT 6A Keystone Module, unshielded, toolfree installation

Features

- Cable entry: Rear side
- Material housing: Abs halogen free, UL 94 V0
- Contacts: Phosphor, bronze
- Coating of contacts: Nickel, gold plated
- Operating temperature: -10 °C up to +50 °C
- Material circuit board: FR4, 1.2 mm
- Mating cycles: ≥ 750
- RJ45 outlet for mounting in Patch Panel
- IDC contacts: Phosphor, bronze
- Layer: 50 µm gold over 40 µm nickel
- Cable connection type: Tool free with cable hatch for strong/flexible conductions AWG 23-26
- Wiring standard: EIA/TIA 568 A/B
- Conformity: Category 6_A / 10GBase-T Channel, ANSI/EIA/TIA 568C.2.1:2002, ISO/IEC 11801:2002
- Dimensions: 35x25x17 mm
- Weight: ca. 12 g
- Compact design allows the installation of 24 pieces in a row of 483 mm (19") 1U Panels
- Opening dimensions according to Keystone standard 19.35x14.8 mm

Product Overview

The Keystone Module "DN-93606" from DIGITUS® is unshielded and provides with tool free installation best performance and link quality for your network. The compact design allows the installation of 24 pieces in a row of 483 mm (19") 1U Panels It is conform to Category 6_A / 10GBase-T Channel, ANSI/EIA/TIA 568C.2.1:2002, ISO/IEC 11801:2002 and certificated by GHMT.

Product Number Information

DN-93606 DIGITUS® CAT 6A Keystone Module, unshielded, RJ45 to LSA, toolfree installation, incl. cable tie

Product Images



Technical Drawings

