

DIGITUS[®] CAT 6_A Keystone Modul, shielded



✓ Category: 6 _A
✔ Shielded
✔ 500 MHz
✔ RJ45 jack

Abstract DIGITUS® CAT 6A Keystone Module, shielded, RJ45 to LSA

Features

- Conctacts: Phoshor, bronze
- Coating of contacts: Nickel, gold plated 0.5 $\boldsymbol{\mu}$
- 360° contacting of cable shield for improved EMV protection
- Operating temperature: -10 °C up to +60 °C
- Material circuit board: FR4, UL 94V-0, 1.45 mm
- Mating cycles: ≥ 750
- RJ45 outlet for mounting in Patch Panel
- Compact design allows the installations of 24 pieces in a row of 483 mm (19") 1U Panels
- Opening dimensions according to Keystone standard 19.35x14.8 mm
- Tool free connection via LSA, color coded according EIA/TIA 568 A&B
- Easy mounting in frame adapter sheets, mounting frames, panels and table housings due to short design
- POE+ according to IEEE 802.3at

Product Overview

The Item "DN-93616" from DIGITUS[®] is a shielded CAT 6_A Keystone Module which provides best performance and link quality for your network.

The compact design allows the installations of 24 pieces in a row of 483 mm (19") 1U Panels. A tool free connection takes place via LSA, color coded according EIA/TIA 568 A&B.


Product Number Information

DN-93616 DIGITUS CAT 6_A Keystone Module, 500 MHz acc., ISO/IEC 11801:2002 AM2:2009/09





Product Images





Technical Drawings





Assmann Electronic GmbH, Auf dem Schüffel 3, 58513 Lüdenscheid, Germany, info@assmann.com, printing errors, falsities and technical changes remain reserved