



Wireless HDMI Transmitter (additional transmitter unit for DS-55319)



Quick Installation Guide DS-55320

Table of Contents

1. Introduction	3
2. Main Features	4
3. Package Content.....	5
4. Product Features	5
5. Product Specification.....	6
6. Overview.....	8
6.1 Transmitter Unit	8
7. Streaming.....	9
7.1 Streaming from Transmitter	9
8. Pairing Transmitter and Receiver	9

1. Introduction

With the Wireless Presentation System, you can wirelessly transmit HDMI video and audio signals in Full HD over a distance of up to 50 m with an unobstructed view. Operation and installation are super simple. Real Plug & Play - Just plug in and get started. With additional transmitters (DS-55320), the set can be extended to up to 16 transmitter units (total). Switch to the desired transmitter quickly and easily at the press of a button in order to reproduce your content. You can also share content directly from your mobile device (smartphone/table) using your device's OS directly, no additional app required. Transmitter and receiver can be supplied with power via your device's HDMI connection (> 500 mAh required). To have a safe and stable operation, we recommend to use always the Micro USB cables for power supply of TX and RX.

Thanks to the compact design of the transmitter and receiver, installation is easy, quick and can be customized - the perfect solution for meeting and conference rooms.

2. Main Features

- Wireless HDMI signal transmission up to 50 m (with unobstructed view)
- With this transmitter unit, extend the Wireless Presentation System (DS-55319) to up to 16 transmitters
- Switch to the desired transmitter quickly and easily at the press of a button in order to reproduce your content
- Supports resolutions up to Full HD (1080p / 60 Hz)
- Easy operation and handling thanks to Plug & Play - Just plug in and get started
- Transmitter can be supplied with power via your device's HDMI connection (> 500 mAh required). To have a safe and stable operation, we recommend to use always the Micro USB cables for power supply of TX and RX.

3. Package Content

- 1x Transmitter unit
- 1x Micro USB cable (80 cm)
- 1x HDMI extension cable (15 cm)
- 1x QIG

4. Product Features

Features	Description
Plug and play	Simply connect the transmitter with the PC HDMI ports and connect the receiver with the screen, the transmitter and receiver will connect automatically
App Free	DS-55320 doesn't need any software or app installation, no setup, no IT team
All in one	Supports also Blu-ray / DVD player, media player and any device with HDMI jack
Multi-user mode	Up to 16 user's presentation at one time
Auto Channel Selection	The Wireless HDMI Transmitter will select the best Wi-Fi channel automatically after power on to ensure streaming smoothly

Fast Speed with 5G AC MIMO Technology	The Wireless HDMI Transmitter comes with the fast 802.11ac MIMO technology which increases Wi-Fi speeds by allowing a pair of wireless devices to simultaneously send or receive multiple data streams
1080p60 High Video Quality	DS-55320 supports 1080p resolution, which means much more clear pictures, rich in details and texture compared with 720p.
High Security Protection	No worries about the data security, Click & Present Mini supports AES 128-bit security encryption and WPA2/WPA-PSK/WPA2-PSK authentication protocol to protect data. HDCP is supported to protect the content


5. Product Specification

Feature	
Video Input	1920x1080 (1080p60/50/30/25/24, 1080i60/50) 1280x720 (720p60/50) 720x576 (576p50) 720x480 (480p60)
Video output	Up to Full HD, 1080p/60 Hz
Audio	Stereo, quality 16bits 48KHz
Wireless Channel	IEEE 802.11ac, 5GHz, 2T2R
Latency	Around 120ms latency
HDMI Version	HDMI 1.4 with HDCP1.3

Authentication Protocol	WPA2 (WPAS-PSK / WPA2-Enterprise)
Security	AES 128 bit
Platform supported	Windows, macOS
Distance	About 50 meters in the clear line of sight
Transmitter	
Interface	HDMI in jack x 1, micro USB x 1, button x 1
LED	Red and Blue
Switch Button	1 x
Power Supply	DC5V/0.5A
Power Consumption	About 2,5 W
Dimension	83 x 32 x 13mm
Weight	27.1 g
Temperature Range	
Operating	0°C to +40°C (+32°F to +104°F)
Storage	-10°C to +60°C (+14°F to +140°F)
Humidity	
Operating	10% to 80% relative humidity
Storage	5% to 90% relative humidity

6. Overview

6.1 Transmitter Unit



1. HDMI in	Connect source devices, like with a computer or other devices with HDMI, the HDMI in also supports 5V power if the source devices has HDMI with a 5V output
2. Button	Short press: start to cast Long press: long press up to 10 seconds for factory reset
2. LED	To display different statue
3. Micro USB	For power supply

LED indicator of the Transmitter Unit	Description
Static red	Transmitter Unit system is booting on
Flashing red	Transmitter is searching for Receiver
Flashing blue	Waiting for connection
Static blue	Connected and started to present
Purple	No HDMI in

7. Streaming

7.1 Streaming from Transmitter

1. Connect the Micro-USB cable with the transmitter and PC (recommended)
2. Connect the transmitter HDMI Unit to a PC HDMI port
3. The LED indicator of the Transmitter will turn red when it's booting up
4. The LED indicator will become blue and flashing when it is ready to stream
5. Click the button to start casting, the LED indicator will become constant blue

8. Pairing Transmitter and Receiver

The set DS-55319 includes one receiver and one transmitter, which are paired before shipment. Normally you don't need to pair them again.

However, if you buy an additional transmitter (DS-55320) or need to re-pair, you need to follow the instruction below to pair the new transmitter with the receiver.

1. Ensure that previously connected transmitters are powered off and not connected to the receiver.
2. Power on the receiver via Micro-USB/Wifi cable and connect with display. Then connect the receivers HDMI plug with the display.
3. Power on the transmitter via Micro-USB cable and connect with the PC first. Then connect the HDMI plug with the PC.

4. The LED turns to flash red, then press the button up to 5 seconds till the LED become fast flashing red, this means the transmitter unit is in factory reset mode.
5. Wait around 15 seconds, the button light of Transmitter Unit will turn to constant blue from the red light, and the pair successful message will be displayed on the Receiver Unit screen.

Remark:

Please make sure that no other transmitter is connected to the receiver when you pair a new transmitter, please ensure to power off all other previously installed transmitter first

Frequency Range & Maximum Transmit Power

WiFi Standard: 802.11b/g/n/ac 5G WiFi

Channel: 36, 40

Core Frequency: 5180, 5200

Range: 5170 ~ 5210MHz

Bandwidth: 20/40MHz

Transmitter power: 13 dBm max

SW version: TX: 2.3.9

HW version: S100TX-LC01-01

Important safety instructions

Please read the following safety instructions carefully before installation and operation:

6. Observe all warnings and instructions concerning this device
7. Do not expose the device to rain, moisture, vapors or liquids
8. Do not insert any objects into the device
9. Do not attempt to repair the unit yourself or open the cabinet.
Risk of electric shock!
10. Ensure adequate ventilation to prevent damage due to overheating
11. Turn off the power supply and make sure the environment is safe before installation
12. In the event of thunderstorms, there is a risk of lightning strike and damage to connected electrical equipment due to overvoltage
13. Do not install this device during a thunderstorm
14. Disconnect the device from the connected electrical appliances during a thunderstorm
15. Use the device inside buildings only
16. Return the device to your dealer in case of repair
17. Dust, moisture, vapors and strong cleaning agents or solvents can damage the device
18. Disconnect the device from the power supply and the connected devices before cleaning
19. Clean the device with a lint-free cloth

Disclaimer

The terms HDMI and HDMI High-Definition Multimedia interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.

Hereby ASSMANN Electronic GmbH declares that the Declaration of Conformity is part of the shipping content. If the Declaration of Conformity is missing, you can request it by post under the below mentioned manufacturer address.

www.assmann.com

Assmann Electronic GmbH

Auf dem Schüffel 3

58513 Lüdenscheid, Germany

