ednet.

USB CAR CHARGER, 3 Port



Manual 84119

SPECIFICATIONS:

- Input voltages: 12-24V DC
- USB output voltage: 5V DC
- Total USB output current: 5.1A max
- USB ports: 1x 1A, 1x 2A,1x 2.1A
- CE, FCC, RoHS
- USB car charger for all smartphones, tablets, cameras, iPhone®, iPad® etc.
- This car charger is with fuse, short circuit protection, LED light indicator

HOW TO USE:

- Plug the USB car charger 84119 into the cigarette lighter port or the vehicle's power outlet.
- The power indicator of 84119 will be lighten up
- Plug the USB cable of music player or devices what you wanted to charge into the charger

FEATURES:

- Certification: CE
- With RoHS Directive-compliant
- Light and convenient plug-in
- LED indication
- High efficiency
- High reliability

WORKING ENVIRONMENTAL:

- Operating temperature: 0 to 40° C
- Storage temperature: -20 to 65° C
- Operating humidity: 10 to 95% RH
- Storage humidity: 10 to 95% RH

PROTECTIONS:

- Over-voltage protection
- Over-current protection
- Short-circuit protection
- Overload protection

DESCRIPTION:

- Built-in IC chip, 100% full loading burning test
- 2.1A / 2A for tablet PCs, 1A for smartphones
- Wide input voltage range
- Compact size and lightweight